### Certificate No.: 2531-CPR-CXA10228

Issue date: 2018-08-07



### **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

#### **Domestic Group 6**

Scope: Resilient, textile and laminate floor coverings for interior use

The product fulfils the essential characteristic of **reaction to fire**:

Class C<sub>fl</sub>-s1

Intended use: Flooring

Placed on the market under the name or trade mark of:

Bentzon Carpet ApS Fabriksvej 15 5500 Middelfart Denmark

and produced in the manufacturing plant:

**CPA20011** 

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 14041:2004 : Resilient, textile and laminate floor coverings – Essential

EN 14041:2004/AC:2006 characteristics

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2018-08-07.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

This certificate was first issued 2018-08-07.

Per Lyster Responsible for evaluation Dan Bluhme Responsible for certification decision

The certificate shall be reproduced in extenso – extracts only with written permission from DBI Certification A/S.

Prod. Reg. Nr. 7023

# Certificate No.: 2531-CPR-CXA10228

Issue date: 2018-08-07



Annex 1

### **EXTENT**

Туре	Description		
Daria	Flat wowen		
Geysira Elfur	Pile: 100 % wool, 600g/m <sup>2</sup>		
Geysira Joekull	Rear side: Cotton		
Jasmin	Total height: 3,5mm		
	Pile height: 3,0mm		
	Total weight: 1800g/m <sup>2</sup>		
Field of application	The carpet is to be mounted on a substrate of classes A1 or A2-s1,d0 at least 6 mm thick and with density equal to or greater than 1350 kg/m³ with a vinyl acetate copolymer dispersion adhesive, application rate: 300 – 350 g/m² (wet).		

## Certificate No.: 2531-CPR-CXA10228

Issue date: 2018-08-07



#### Annex 2

### **TEST DOCUMENTATION**

Accredited Laboratory	Report no.	Date
DBI	PFA11189A	2018-07-17
DBI	PCA10491A	2018-07-17

### Annex 3

### **TECHNICAL BASIS**

Designation	Identification	$\Lambda$	Date
			7
Daria	V13042018.1		2018-04-13
Geysira Elfur	V13042018.1		2018-04-13
Geysira Joekull	V13042018.1		2018-04-13
Jasmin	V13042018.1		2018-04-13
Supplementary information			2018-05-25

Prod. Reg. Nr. 7023